



Exterior

Waterproof

11020

**Product Description:**

Storm System Waterproof is a transparent sealer that penetrates the surface of dry, porous wood surfaces to help prevent moisture penetration and water damage. This product dries clear and allows the wood surface to age naturally. This product will protect against salt water. For new construction, prevent water damage by applying this product immediately after installation.

**Recommended Use:**

Shingles, Shakes, Siding, Fencing, Decks and Rails, Timbers, Architectural Millwork, Sills, Outdoor Furniture, Log Homes, Storage Sheds, Kennels, Plywood Lumber, Paneling

**Application:**

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

To allow for penetration, surfaces must be thoroughly dry, clean, and free from other coatings that may prevent penetration. Always test a small area before application for desired results before coating the entire surface.

Apply at temperatures above 50° F using a suitable brush, roller, pad applicator or flooding spray. Use sufficient material to saturate the surface. Do not apply a second coat over a dry first coat. It is acceptable to apply a second coat via a wet on wet method.

**Architectural Specifications:**

Wood: one or two coats (wet on wet) Storm System Waterproof No. 11020

**Precautions:**

Do not re-coat with paint or other coatings.

**Safety Information:**

Keep out of reach of children. Do not take internally.

\*14-19 sec. #2 Zahn

\*\*48 hrs to reach full water repellency

**Product Specifications:**

**Type:** Carboxylate Complex  
**Exposure:** Exterior  
**Specular Gloss:** N/A@ 60° ±  
**Volume Solids:** 11.9 % ±2  
**Solids by Weight:** 12.5 % ±2  
**Vehicle:** 100 % ±2  
**Pigment:** 0 % ±2  
**Dry Film Thickness:** <1 mills  
**Viscosity @ 77 °F:** \* KU ±5  
**Maximum VOC:** 100 g/liter  
**Flash Pt °F:** Non-combustible  
**Thinner:** Water  
**Clean Up:** Soap & Water

**Available Colors and Bases:**

Clear

**Available Package Sizes:**

Gallon 5 Gallon

(Weight Per Gallon: 8.4 lbs. ± .5 lb)

**Drying Times:**

**To Touch:** N/A\*\* hrs.  
**To Handle:** N/A\*\* hrs.  
**To Recoat:** 1/2 hr -6 hrs.  
(@ 70-77 °F, 50% R.H.)

**Surface Spread Rate:**

**Smooth:** 300 s.f./gal.  
**Porous:** 90 s.f./gal.  
(Spray Application is 50% of above)

**Tools and Equipment:**

**Brush -**  
Synthetic, Nylon or Polyester  
Pad Application

**Roller -**  
3/8" Nap Synthetic Fiber

**Airless Spray-**  
Flooding spray