



**Exterior**

**Wood Life Extender**

**11024**

**Product Description:**

Storm System Wood Life Extender has been developed to prolong the life of wood and wood products. This clear zinc naphthenate is designed to retard warping, swelling, shrinking and checking of previously unfinished woods. This product repels moisture and resists the growth of mildew and other fungus on the cured surface. Wood surfaces protected with this product will be affected by UV light unless topcoated with pigmented paints or stain systems. This product can be recoated after 24 hours dry with either latex or stain systems.

**Recommended Use:**

UNFINISHED WOOD DECKS, TIMBER, SILLS, ARCHITECTURAL MILLWORK, WINDOW SASH, GUTTERS, SIDING, PLYWOOD, CANVAS.

**Application:**

Storm System Wood Life Extender No. 11024 should be applied liberally by brush, roller or spray or by dipping in a container. The more wood stabilizer absorbed, the more effective the protection. Do not thin. Material is supplied at proper application consistency. Wood immersion should be for three minutes if dipped. A single coat is recommended for surfaces to be painted or stained. On porous or rough wood that will remain clear, a second coat is recommended within the hour. EXCESS MATERIAL NOT ABSORBED SHOULD BE WIPED OFF WITH A DAMP RAG WITHIN MINUTES. Clean equipment, preferably with mineral spirits, immediately after completion of job for fast cleanup.

**Architectural Specifications:**

- UNFINISHED WOOD DECKS, TIMBER, SILLS, MILLWORK, WINDOW SASH, GUTTERS, SIDING, PLYWOOD
- One or two coats of Storm System Wood Life Extender applied full body.

NOTE: Most woods only require one coat, but soft porous woods can be recoated if necessary in two hours. Extra wood extender that does not penetrate should be wiped off with a clean cloth.

Dipping - Best method of application Immerse wood for three minutes in Storm System Wood Life Extender No. 11024

**Precautions:**

Remove all mildew before application with Storm System Mold and Mildew Stain Remover. Do not use over previously sealed, painted or varnished surfaces. Do not apply over bark. Do not apply on surfaces directly in contact with soil or water. Do all sanding, drilling and cutting before application. All previous finishes must be removed and surface neutralized before use. Not for interior use.

**Safety Information:**

CAUTION! COMBUSTIBLE! Use only with adequate ventilation. Keep out of reach of children. Do not take internally. Close container after each use.

\*Low solids coating.

**Product Specifications:**

**Type:** Zinc Naphthenate  
**Exposure:** Exterior  
**Specular Gloss:** @ 60° ±  
**Volume Solids:** 7.5 % ±2  
**Solids by Weight:** 8.6 % ±2  
**Vehicle:** 100 % ±2  
**Pigment:** % ±2  
**Dry Film Thickness:** mils  
**Viscosity @ 77 °F:** KU ±5  
**Maximum VOC:** 50\* g/liter  
**Flash Pt °F:** 103  
**Thinner:** Mineral Spirits  
**Clean Up:** Mineral Spirits

**Available Colors and Bases:**

Clear

**Available Package Sizes:**

Gallon 5 Gallon

(Weight Per Gallon: 8.3 lbs. ± .5 lb)

**Drying Times:**

**To Touch:** 24 hrs.  
**To Handle:** hrs.  
**To Recoat:** hrs.  
 (@ 70-77 °F, 50% R.H.)

**Surface Spread Rate:**

**Smooth:** 300 s.f./gal.  
**Porous:** 100 s.f./gal.  
 (Spray Application is 50% of above)

**Tools and Equipment:**

**Brush -**  
 Natural Bristle

**Roller -**  
 Medium Nap

**Airless Spray -**  
 .001-.013