



Exterior

Storm System™ Wood Brightener/ Neutralizer

No. 10310

Product Description:

Storm System Wood Brightener/Neutralizer is a concentrated product for brightening exterior, natural wood surfaces that have darkened. Wood Brightener/Neutralizer is ideal for use on pressure treated wood, cedar, redwood and other tannin woods. This product provides excellent results and does not contain any bleach, phosphates or any ozone depleting ingredients.

Recommended Use:

Exterior bare wood decks, siding, fencing and patios.

Application:

Lightly sanding surface will remove residual wood fibers and help coating penetration and adhesion. Wait until surface is thoroughly dry before applying this product.

Application:

Dilute Wood Brightener/Neutralizer in clean tap water at a MAXIMUM ratio of 7 to 1; 7 parts water to 1 part Brightener/Neutralizer.

Do not mix or use with any metal containers or applicators. Test dilution on an inconspicuous area prior to general use to determine proper solution strength. After determining appropriate solution strength, apply liberally by brush, roller or plastic pump-style sprayer. Apply to a cool, dry surface. On vertical surfaces, start application from the bottom. Wait 10-15 minutes, lightly agitate surface and rinse or power wash. If wood appears blotchy when dry, re-apply to achieve desired results. Avoid contact with metal, lawn furniture and fabric. Allow surface to dry thoroughly before applying a new finish. To ensure proper adhesion, lightly sand the surface before applying a new finish.

Let product stand 10-15 minutes. Do not allow product to dry before rinsing. If necessary, lightly mist with water to keep wet. Clean tools and equipment immediately using soap and water.

Precautions:

CAUTIONS! CORROSIVE. CAUSES SEVERE IRRITATION AND BURNS TO EYES, SKIN AND RESPIRATORY TRACT. Contact with eyes may cause severe burns with possible corneal damage or blindness. Skin contact can cause severe irritation and burns. Inhalation of vapors and mist may cause irritation to eyes and respiratory tract. High concentrations can produce severe irritation and burns to respiratory tract. Ingestion may cause gastrointestinal corrosion, vomiting and diarrhea.

Use only with adequate ventilation. Do not breathe spray mist, vapors or sanding dust. Avoid contact with eyes and prolonged or repeated contact with skin. Wear eye and full face protection. Wear impervious gloves, apron, boots and other clothing needed to prevent contact. If spraying (only outdoors) use a NIOSH approved respirator. If you experience eye watering, headaches or dizziness, increase fresh air or wear properly fitted vapor/particulate NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for use.

DO NOT MIX OR USE with other household cleaners or chemicals. Close container after each use. Wash thoroughly with soap and water after each use. Exercise caution when working on surfaces that are wet. Wet surfaces are extremely slippery.

WARNING: This product contains a chemical known to the state of California to cause cancer and birth defects, or other reproductive harm.

Safety Information:

KEEP OUT OF REACH OF CHILDREN. PROTECT FROM FREEZING. First Aid: In case of eye contact, immediately flush with water for 30 minutes while lifting upper and lower lids. In case of skin contact, wash with soap and water immediately, remove contaminated clothing and launder before reuse. If affected by inhalation of vapors or spray mist, remove to fresh air. If ingested and victim is conscious, give one glass of water or milk to dilute. DO NOT INDUCE VOMITING. Never give anything by mouth to unconscious or convulsing victim. In all cases of exposure, call a physician immediately.

In case of spill, absorb with inert material and dispose of properly.

**Per undiluted gallon. Overall coverage will vary depending on dilution strength, substrate and application method.

Refer to Material Safety Data Sheet at www.stormsystem.com for further safety and handling information.

Manufactured for: Storm System – A division of California Products Corporation

Product Specifications:

Type: Maintenance Cleaner*
Exposure: Exterior
Flash Pt °F: Non-combustible
Thinner: Water
Clean Up: Soap & Water

Surface Spread Rate:

100-200** s.f./gal.

Available Package Sizes:

Gallon

(Weight Per Gallon 9.0 lbs. ± .5 lb)

Tools and Equipment:

Airless Spray -
 Pump-Style Garden sprayer

Roller

Brush