



Exterior

Storm System® Wood Stripper

No. 50420

Product Description:

Storm System Wood Stripper is a concentrated product for the removal of oil based stains, clear finishes, water based stains and latex products. Wood Stripper provides excellent results and does not contain any bleach, phosphates or petroleum solvents. Use this product in place of ineffective bleach products or hazardous solvent based compounds. It is a proven stripper of stains, finishes and discolorations that are caused by sunlight, moisture, mold, mildew and ground in dirt and grease on natural wood surfaces.

Recommended Use:

Painted or stained decks, siding, fencing, and patios.

Application:

Prior to application, remove all furniture, metal fixtures and children's toys from the area. Thoroughly wet down plants and vegetation before and after application to avoid damage. Wait until surface is thoroughly dry before applying stain or any other coating. Lightly sanding surface will help coating penetration and adhesion.

Test dilution on an inconspicuous area prior to general use to determine proper solution strength. Storm System Wood Stripper concentrate makes up to 5 gallons of solution.

(Use clean tap water)

Multiple Coats – Solid Color or Semi Solid Stain DO NOT DILUTE

Weathered – Solid Color or Semi Solid Stain Mix 1 gallon of Wood Stripper with 1 gallon of water

Semi Transparent Stain – Mix 1 gallon of Wood Stripper with 2 gallons of water

Transparent Stain – Mix 1 gallon of Wood Stripper with 3 gallons of water

Clear Finish – Mix 1 gallon of Wood Stripper with 4 gallons of water

After determining appropriate solution strength, apply to a cool, dry surface. Apply this product liberally to the surface with plastic sprayer. On vertical surfaces, start application from the bottom.

Let product stand 10-30 minutes or until coating has softened or lifted. Lightly mist with water or re-apply Wood Stripper to prevent product from drying. Agitate product with a stiff brush and thoroughly rinse or power wash to remove coating. Use Storm System Wood Brightener/Neutralizer to neutralize any remaining stripper and brighten wood darkened by stripper or age. Allow surface to dry thoroughly before applying a new finish. To ensure proper adhesion, lightly sand the surface before applying a new finish.

Stand Time:

Let product stand 10-30 minutes or longer without drying depending on age and type of finish being removed. Do not allow product to dry before rinsing. If necessary, lightly mist with water to keep wet.

Clean tools and equipment immediately using soap and water.

Precautions:

CAUTIONS! CORROSIVE. CAUSES SEVERE IRRITATION AND BURNS TO EYES, SKIN AND RESPIRATORY TRACT. Contact with eyes may cause severe burns with possible corneal damage or blindness. Skin contact can cause severe irritation and burns. Inhalation of vapors and mist may cause irritation to eyes and respiratory tract. High concentrations can produce severe irritation and burns to respiratory tract. Ingestion may cause gastrointestinal corrosion, vomiting and diarrhea.

Use only with adequate ventilation. Do not breathe spray mist, vapors or sanding dust. Avoid contact with eyes and prolonged or repeated contact with skin. Wear eye and full face protection. Wear impervious gloves, apron, boots and other clothing needed to prevent contact. If spraying (only outdoors) use a NIOSH approved respirator. If you experience eye watering, headaches or dizziness, increase fresh air or wear properly fitted vapor/particulate NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for use.

DO NOT MIX OR USE with other household cleaners or chemicals. Close container after each use. Wash thoroughly with soap and water after each use. Exercise caution when working on surfaces that are wet. Wet surfaces are extremely slippery.

Safety Information:

KEEP OUT OF REACH OF CHILDREN. PROTECT FROM FREEZING. First Aid: In case of eye contact, immediately flush with water for 30 minutes while lifting upper and lower lids. In case of skin contact, wash with soap and water immediately, remove contaminated clothing and launder before reuse. If affected by inhalation of vapors or spray mist, remove to fresh air. If ingested and victim is conscious, give one glass of water or milk to dilute. DO NOT INDUCE VOMITING. Never give anything by mouth to unconscious or convulsing victim. In all cases of exposure, call a physician immediately.

In case of spill, absorb with inert material and dispose of properly.

**Per undiluted gallon. Overall coverage will vary depending on dilution strength, substrate and application method.

Refer to Material Safety Data Sheet at www.stormsystem.com for further safety and handling information.

Product Specifications:

Type: Maintenance Cleaner*

Exposure: Exterior

Flash Pt °F: Non-combustible

Thinner: Water

Clean Up: Soap & Water

Surface Spread Rate:

100-200** s.f./gal.

Available Package Sizes:

Gallon

(Weight Per Gallon 9.0 lbs. ± .5 lb)

Tools and Equipment:

Airless Spray -

Pump-Style Garden sprayer

Brush