



Exterior

**100% Acrylic Topcoat
Transparent No. 11550**

Product Description:

This product is a 100% acrylic clear protective coating for use over Storm System CATEGORY 1 CATEGORY 2 and CATEGORY 3 products. This product is an ideal clear finish to enhance the beauty and longevity of Storm System CATEGORY 1, 2 & 3 products and can also be used to refresh the look for CATEGORY 1, CATEGORY 2 and CATEGORY 3 stained surfaces after weathering 1 or more years.

Recommended Use:

For Pressure Treated and Conventional Woods / Sun Decks / Wood Screening / Patios / Siding / Fencing / Benches / Open Porches / Outdoor Furniture / Railings and Posts / Wood Pool and Garden Enclosures

Application:

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.
This product is of proper consistency as packaged is to be applied without thinning under normal environmental application conditions.

Surface Preparation:

All surfaces must be clean and thoroughly dry before application of this product. Always test a small area before application to the entire surface. All mildewed areas should be scrubbed with Storm System All Surface Mold & Mildew Stain Remover and thoroughly rinsed. New pressure treated wood should be scrubbed with Storm System All Surface Cleaner to remove all surface deposits. Rinse thoroughly and allow to dry. When using as a topcoat over Storm System CATEGORY 1, CATEGORY 2 or CATEGORY 3 Dual Dispersion Stains, be sure to follow application instructions.

Application:

Stir thoroughly. Apply with synthetic brush, roller or spray. Clean brushes and equipment with soap and water and remove spatters immediately after completion of the job. Not for below grade application.

Architectural Specifications:

Use this product as a clear topcoat over Storm System CATEGORY 1 Dual dispersion Clear Finish #11540, CATEGORY 2 Dual Dispersion Stain #225XX Series and CATEGORY 3 Dual Dispersion Semi Solid Stain #34595 for longer durability and greater protection.

Precautions:

Temperatures of both air and surface should be at least 50°F (10°C) during application and drying time. Do not apply in hot sunlight or if wet weather is expected within 48 hours. Surfaces are slippery when wet. Use caution when walking on wet surfaces during application.

Safety Information:

Keep out of reach of children. Do not take internally. Close container after each use.

Product Specifications:

Type: 100% Acrylic Latex
Exposure: Exterior
Specular Gloss: N/A@ 60° ±2
Volume Solids: 24.4 % ±2
Solids by Weight: 26.5 % ±2
Vehicle: 100.0 % ±2
Pigment: 0 % ±2
Dry Film Thickness: 1.0 mils
Viscosity @ 77 °F: 80 KU ±5
Maximum VOC: 100 g/liter
Flash Pt °F: Non-combustible
Thinner: Water
Clean Up: Soap & Water

Available Colors and Bases:

Clear

Available Package Sizes:

Quart Gallon 5 Gallon

(Weight Per Gallon: 8.6 lbs. ± .5 lb)

Drying Times:

To Touch: 4 hrs.
To Handle: 4-6 hrs.
To Recoat: 16 hrs.
 (@ 70-77 °F, 50% R.H.)

Surface Spread Rate:

Smooth: 200-400 s.f./gal.
Porous: 150-350 s.f./gal.
 (Spray Application is 50% of above)

Tools and Equipment:

Brush -
Synthetic

Roller -
Synthetic
Medium Nap

Airless Spray -
.011 to .013