



Exterior

High Build Finish - Semi-Solid

341XX

### Product Description:

This product decorates and protects exterior wood, siding from weather and temperature changes. This product can be used on new wood, previously stained wood with proper preparation. Apply one coat over previously stained surfaces but two coats will provide maximum protection on new or unfinished wood.

### Recommended Use:

Wood Siding / Shingles / Clapboard / Log Siding / Wood Screening / Fencing / Outdoor Furniture

### Application:

**WARNING!** If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

This product is of proper consistency as packaged is to be applied without thinning under normal environmental application conditions.

#### Surface Preparation:

Remove all dust, dirt, or surface contaminants before applying coating. Do not use over previously sealed or varnished surfaces. All surfaces must be clean and thoroughly dry before application of this product. All mildewed areas should be scrubbed with an appropriate mildew killing solution and thoroughly rinsed. New pressure treated wood should be scrubbed with trisodium phosphate (TSP) and water. Rinse thoroughly with clean water and allow to dry completely.

Application: Stir thoroughly. Product application should be under factor-controlled conditions of a machine applicator. Clean tools and equipment immediately with warm soapy water.

### Architectural Specifications:

- Unfinished Wood Siding, Rails, Posts, Fences, Patios, Screening and Outdoor Furniture;  
1 Coat Storm System High Build Finish - Semi-Solid #341XX

- Pressure Treated Wood;  
1 Coat Storm System High Build Finish - Semi-Solid #341XX

Note: Do not use interchangeably on the same substrate with other Storm System products as you may note differences in appearance. Appearance varies with different species of wood. Samples should be tested on the actual wood being used to insure an acceptable appearance.

### Precautions:

Do not apply over wet surfaces. Do not apply when air or surface temperature is below 60°F. Protect from freezing.

### Safety Information:

Avoid contact with skin. Use only with adequate ventilation. Keep out of reach of children. Protect from freezing. Do not take internally. Close container after each use.

First Aid: If swallowed, do not induce vomiting. Call a physician immediately.

### Product Specifications:

**Type:** 100% Acrylic  
**Exposure:** Exterior  
**Specular Gloss:** 40 @ 60° ±3  
**Volume Solids:** 30.7 % ±2  
**Solids by Weight:** 35.6 % ±2  
**Vehicle:** 78 % ±2  
**Pigment:** 6 % ±2  
**Dry Film Thickness:** 1.5 mils  
**Viscosity @ 77 °F:** 65 KU ±5  
**Maximum VOC:** 100g/liter  
**Flash Pt °F:** Non-combustible  
**Thinner:** Water  
**Clean Up:** Soap & Water

### Available Colors and Bases:

Teak	Cedar
Natural	Dark Oak
Butternut	

### Available Package Sizes:

Quart    Gallon    5 Gallon

(Weight Per Gallon: 9.80 lbs. ± .5 lb)

### Drying Times:

**To Touch:** 4 hrs.

**To Stack:** N/A hrs.

**To Recoat:** 8 hrs.

(@ 70-77 °F, 50% R.H.)

### Surface Spread Rate:

**Smooth:** 200-400 s.f./gal.

**Porous:** N/A s.f./gal.

(Spray Application is 50% of above)

### Tools and Equipment:

**Brush -**  
Synthetic, Nylon or Polyester

**Roller -**  
Medium Nap

**Airless Spray -**  
.011 to .013